



OPERATION MANUAL FOR RECHARGEABLE BATTERY



■ **SKC-LB1030S**



■ **SKC-LB1025E**

Note

Battery limited warranty obtains for 6-month by manufacturer. For better durability, fully charge battery at least once while battery without using for 3 months long. All rechargeable batteries are consumable components that become less effective as they chemically age.

Caution

For the safety reason, please only use the same type of charger manufactured by Kilews to recharge this type of battery. Please read  manual carefully and follow all the instructions, also pay attention to all the warning.

KILEWS INDUSTRIAL CO., LTD.

<http://www.kilews.com.tw>

Important Notification

1. Please read  all instructions carefully before operate the rechargeable screwdriver and the charge station. Failure to follow all instructions listed below may result in electric shock fire and/or serious injure.
2. Please fully recharge the battery before assembling with screwdriver.
3. Before insert the battery, switch the Forward/Reverse lever to the middle position, in case of accident.
4. Do not place battery on high shelf. The battery should be placed on a flat and firm place to prevent children from touching.
5. Please do not place rechargeable battery in the poorly ventilated place, nor expose the battery in the dust or metal crumb.
6. Do not expose rechargeable battery directly under sun, high temperature, high humidity , and highly explosive gas .
7. It is forbidden to use different brand of battery other than KILEWS' on the charger.  To disassemble and modify the battery is also not allowed. The use of other than genuine KILEWS battery may result in decreased tool performance and increased maintenance and may invalidate all warranties.
8. Abusing the rechargeable battery may cause the battery damaged. If the liquid leak out due to the damage of the battery, please do not touch with your own buddy. If so, please use tab water to rinse off. If the liquid get into your eye, please contact a doctor immediately.
9. Rechargeable batteries have 6 months warranty. Depends on the frequency of use, the battery capacity gradually shortened (charging time). When the battery unused more than six months, please let battery fully charged once. Otherwise, it will shorten the battery life time and will cause the battery to deactivated and not able to recharge.
10. The best working temperature to recharge the battery is from 0°C to 30°C. When the battery temperature is below 0°C, the battery-liquid inside the rechargeable battery will be frozen, therefore the battery is not able to recharge.
11. Under normal usage, KILEWS battery guaranties 600 recharge times. Battery remains 75% capacity when battery recharge after 1000 times. Each recharge and discharge, battery capacity decreases.

Caution

Risk of Fire and Burns. Do Not Open, Crush, Heat Above 60°C (where is manufacturer's specified maximum temperature) or incinerate. Follow Manufacturer's Instructions.

Icon explanation



Read Manual



Caution



Recycle



No Humidity



No Fire



No Disassemble



No Disposal

Safety Certifications



CE certification

SKC-LB1025E



TUV certification

SKC-LB1030S







CAUTION

Keep the battery away from fire. Avoid the action of short circuit. Never attempt to disassemble the battery pack, Use the designated chargers to charge the battery pack. Risk of explosion if battery replaced by an incorrect type. Dispose of used batteries according to the instructions.

ATTENTION

Gardez la batterie à l'écart du feu. Évitez l'action du court-circuit. Ne tentez jamais de démonter le bloc de batterie, utilisez les chargeurs désignés pour charger la batterie. Risque d'explosion si la batterie est remplacée par un type incorrect. Disposer des piles usagées conformément aux instructions.

Product introduction and specification

Product type	SKC-LB1030S	SKC-LB1025E
Appearance		
Operation steps	  Assemble with coreless screwdriver. Connect to the charge station.	  Assemble with coreless screwdriver. Connect to the charge station.
Battery capacity	3000 mAh	2500 mAh
Color	Black	
Battery type	Lithium-ion rechargeable battery	
Battery weight(g)	194.1	300
Dimensions(mm)	51×46×90 mm	92×75×45 mm
Power(wh)	32.4	27
Nominal voltage	10.8V	
Full charged voltage	12.6V	

Contents

Rechargeable battery	1 PCS
Operation manual	1 PCS
Warranty certification	1 PCS

Caution 
SAVE THE INSTRUCTIONS
DO NOT DESTROY